



Application Procedure EnviroTouch Mould and Odour Inhibitor

Description - EnviroTouch leaves a safe invisible film with encapsulated probiotics and natural actives to protect treated surfaces against mould, biofilm and odour-producing germs. The EnviroTouch actives remain dormant for months when dry. When activated by water, probiotics outcompete mould and other pathogens for food suppressing their growth.

Purpose – outline the process to correctly prepare and apply EnviroTouch to surfaces that are contaminated with mould and bacteria or have a risk of contaminated.

Before starting any work, please review SDS for EnviroTouch found on the web site www.ozsan.com.au

Procedure

Remove gross contamination

The entire area being treated with EnviroTouch needs to be precleaned and all noticeable dirt and debris removed. This can be used by using simple water and a neutral detergent.

Application of EnviroTouch

Odour protection

1/ spray or coat rubbish bins and all surfaces that require residual protection

2/ let dry

3/ reapply every 3-4 weeks

OR Simple pour 50-60 mls of EnviroTouch into Rubbish bin, septic tank or drain

On surfaces contaminated with mould

1/ Bleach with 0.1-2% ammonia (1 part household bleach and 20 parts water)

2/ allow to dry for 15-20 minutes

3/ Spray or apply a coat of EnviroTouch to the newly cleaned surface (25-40 mls per 1 sqm)

4/ A non-tacky coating will dry in 5-10 minutes



Application Procedure EnviroTouch Mould and Odour Inhibitor

For Residual protection (Dilute with water 1:4)

- 1/ Spray or apply a coat of EnviroTouch to the newly cleaned surface (25-40 mls per 1 sqm)
- 2/ A non-tacky coating will dry in 5-10 minutes

For smelly drains

- 1/ The drain being treated with EnviroTouch should be free of bulk waste.
- 2/ Using a foaming gun fill the drain with foam
- 3/ reapply when odour returns

For Cars

- 1/ Clean all carpets and floor mats
- 2/ Dry for 15 minutes
- 3/ Spray or apply a coat of EnviroTouch to the newly cleaned surfaces. (25-40 mls per sqm)
- 4/ a non tacky coating with dry in 5-10 minutes

EnviroTouch should be reapplied every 3-4 months or if odour is noticeable.